

Compliance status of RoHS directive

C: Compliant **S.C:** Compliant (Included RoHS exemption substance) **N:** Non-compliant

Production Status

M: Mass production **U:** Under development **N:** Not for new design **D:** Discontinued

Motor Driver IC (Single Chip Inverter)

◆ **VSP Input Series (Charge pump system)**

Brushless motor application

Type	Voltage (V)		Current (A)		Remarks	RoHS status	Status
	VCC	VSM	Peak	Average			
ECN30110F/P/PN/S	15	250	1.4	1.0	Power on/off sequence-free Embedded Hall amplifiers High-voltage diodes	C	M
ECN30114SP/SPV/SPR	15	250	1.4	1.0	Power on/off sequence-free Embedded Hall amplifiers High-voltage diodes	S.C	M
ECN30210F/P/PN/S	15	600	1.5	0.7	Power on/off sequence-free Embedded Hall amplifiers High-voltage diodes	C	M
ECN30214SP/SPV/SPR	15	600	1.5	0.7	Power on/off sequence-free Embedded Hall amplifiers High-voltage diodes	S.C	M
ECN30216F/P/R/S	15	600	1.5	0.7	Power on/off sequence-free Embedded Hall amplifiers High-voltage diodes Capacitors for top arm power supply	C	M

◆ **Three Input, Six Input Series (Charge pump system)**

Brushless motor, Induction motor application

Type	Voltage (V)		Current (A)		Remarks	RoHS status	Status
	VCC	VSM	Peak	Average			
ECN30620F/P/PN	15	600	2.0	1.0	6-input, Embedded high-voltage diodes	C	M
ECN30622F/P/PN/S/R	15	600	3.0	2.0	6-input, Embedded high-voltage diodes	C	M
ECN30632SP/SPV/SPR	15	600	3.0	2.0	6-input, Embedded high-voltage diodes	S.C	M
ECN30625S/PN	15	600	2.0	1.0	6-input, High-voltage diodes Capacitors for top arm power supply	C	M
ECN30625P/F/R	15	600	2.0	1.0	6-input, High-voltage diodes Capacitors for top arm power supply	C	U
ECN30624PN	15	600	3.0	2.0	6-input, High-voltage diodes Capacitors for top arm power supply	C	M
ECN30624P/F/R	15	600	3.0	2.0	6-input, High-voltage diodes Capacitors for top arm power supply	C	M

◆ **Three Input, Six Input Series (Bootstrap system)**

Brushless motor, Induction motor application

Type	Voltage (V)		Current (A)		Remarks	RoHS status	Status
	VCC	VSM	Source	Sink			
ECN30502S	15	620	0.25	0.4	6-input, Embedded high-voltage diodes, For sensor type	C	M
ECN30552S	15	620	0.25	0.4	6-input, Embedded high-voltage diodes	C	M

Not for New Design

Please ask sales representative in the reference about the substitution version part no.

◆VSP Input Series for driving motor

Type	Voltage (V)		Current (A)		Substitution version part no.	RoHS status	Status
	VCC	VSM	Peak	Average			
ECN30107SP/SPV/SPR	15	250	1.4	1.0	ECN30110F/P/PN ECN30114SP/SPV/SPR	S.C	N

◆Three Input, Six Input Series (Bootstrap system)

Type	Voltage (V)		Current (A)		Substitution version part no.	RoHS status	Status
	VCC	VSM	Source	Sink			
ECN33500FP	15	620	0.25	0.4	ECN30502S	C	N
ECN30551FP	15	620	0.25	0.4	ECN30552S	C	N

Discontinued

Please ask sales representative in the reference about the substitution version part no.

◆VSP Input Series for driving motor

Type	Voltage (V)		Current (A)		Substitution version part no.	RoHS status	Status
	VCC	VSM	Peak	Average			
ECN30105SP/SPV/SPR	15	250	1.8	1.0	ECN30110F/P/PN ECN30114SP/SPV/SPR	S.C	D
ECN30102SP/SPV/SPR	15	250	1.2	0.7	ECN30110F/P/PN ECN30114SP/SPV/SPR	S.C	D
ECN3018SP/SPV/SPR	15	250	1.8	1.0	ECN30110F/P/PN ECN30114SP/SPV/SPR	S.C	D
ECN30108P	15	250	1.4	1.0	ECN30110F/P/PN ECN30114SP/SPV/SPR	S.C	D
ECN30207SP/SPV/SPR	15	500	2.0	1.4	ECN30210F/P/PN/S	S.C	D
ECN30204SP/SPV/SPR	15	500	1.5	0.7	ECN30210F/P/PN/S	S.C	D
ECN3021SP/SPV/SPR	15	500	1.0	0.7	ECN30210F/P/PN/S	S.C	D
ECN3022SP/SPV/SPR	15	500	1.5	0.7	ECN30210F/P/PN/S	S.C	D
ECN30208P	15	500	1.5	0.7	ECN30210F/P/PN/S	S.C	D
ECN30206SP/SPV/SPR	15	500	1.5	0.7	ECN30210F/P/PN/S	S.C	D

◆Three Input, Six Input Series for driving motor

Type	Voltage (V)		Current (A)		Substitution version part no.	RoHS status	Status
	VCC	VSM	Peak	Average			
ECN33101SP/SPV/SPR	15	250	1.4	1.0	ECN30620F/P/PN ECN30625S	S.C	D
ECN33201SP/SPV/SPR	15	500	1.5	0.7	ECN30620F/P/PN ECN30625S	S.C	D
ECN33202SP/SPV/SPR	15	500	2.0	1.4	ECN30622F/P/PN/S/R ECN30632SP/SPV/SPR ECN30624PN	S.C	D
ECN30611SP/SPV/SPR	15	250	1.4	1.0	ECN30620F/P/PN	S.C	D
ECN3061SP/SPV/SPR	15	250	1.8	1.0	ECN30620F/P/PN	S.C	D
ECN30604SP/SPV/SPR	15	500	2.0	1.4	ECN30622F/P/PN	S.C	D
ECN30601SP/SPV/SPR	15	500	1.5	0.7	ECN30620F/P/PN	S.C	D
ECN3063SP/SPV/SPR	15	500	1.0	0.7	ECN30620F/P/PN	S.C	D
ECN3064SP/SPV/SPR	15	500	1.5	0.7	ECN30620F/P/PN	S.C	D
ECN3067SL/SLV/SLR	15	500	5.0	2.5		—	D
ECN30671SP/SPV/SPR	15	500	3.0	1.5	ECN30622F/P/PN	S.C	D
ECN30603SP/SPV/SPR	15	500	1.5	0.7	ECN30620F/P/PN	S.C	D

Discontinued

Please ask sales representative in the reference about the substitution version part no.

◆ Gate Driver IC (Predriver IC for IGBT or Power MOSFET Drive)

VSP input, Three input, Six input series

Type	Voltage (V)		Current (A)		Substitution version part no.	RoHS status	Status
	VCC	VSM	Source	Sink			
ECN30300S	15	250	top arm 0.10 bottom arm 0.20	top arm 0.25 bottom arm 0.20		C	D
ECN30301S	15	250	top arm 0.10 bottom arm 0.20	top arm 0.25 bottom arm 0.20		C	D
ECN3030F	15	250	top arm 0.05 bottom arm 0.2	top arm and bottom arm 0.2	ECN30551FP	C	D
ECN3031F	15	250			ECN30551FP	C	D
ECN3035F	15	500	top arm 0.05 bottom arm 0.2	top arm and bottom arm 0.2	ECN30551FP	C	D
ECN3036F	15	500			ECN30551FP	C	D
ECN3053F	15	620	0.25	0.5	ECN30551FP	C	D
ECN3054F	15	620	0.25	0.5	ECN30551FP	C	D
ECN30531F	15	620	0.25	0.5	ECN30551FP	C	D
ECN30541F	15	620	0.25	0.5	ECN30551FP	C	D
ECN33550FP	15	620	0.25	0.4	ECN33500FP, ECN30551FP	C	D

High Voltage Analog Switch (HVMUX)

◆Ultrasound Imaging System/NDT application

Type	Voltage (V)		Clock (MHz)	Input Signal Range(V)	Analog Switch On Resistance	Channel	Bleed Resistor	PKG	RoHS status	Status
	VDD	VPP-VNN								
ECN3290TF	5	220	10	VNN+10~VPP-10	22Ω (typ.)	8	No	LQFP48	C	M
ECN3294TF	3.3/5	220	20	VNN+10~VPP-10	19Ω (typ.)	8	User selectable (one side of SW)	LQFP48	C	M
ECN3296TF	3.3/5	220	30 @5V 20 @3.3V	VNN~VPP	19Ω (typ.)	16	No	LQFP48	C	M
ECN3297TF	3.3/5	220	30 @5V 20 @3.3V	VNN~VPP	19Ω (typ.)	16	Yes (Both side of SW)	LQFP48	C	M
ECN3298TF	3.3/5	220	30 @5V 20 @3.3V	VNN~VPP	19Ω (typ.)	16	Yes (SW_B side)	LQFP48	C	M

HVMUX (No dedicated high voltage power supplies required)

◆Ultrasound Imaging System/NDT application

Type	VDC (V)	Logic I/F(V)	Clock (MHz)	Input Signal Range(V)	Analog Switch On Resistance	Channel	Bleed Resistor	PKG	RoHS status	Status
ECN32910TF	10~15	3.3/5	30 @5V 20 @3.3V	-100~+100	18Ω (typ.)	16	No	LQFP48	C	M
ECN32911TF	10~15	3.3/5	30 @5V 20 @3.3V	-100~+100	18Ω (typ.)	16	Yes (Both side of SW)	LQFP48	C	M

Discontinued

High Voltage Analog Switch (HVMUX)

◆Ultrasound Imaging System/NDT application

Type	Voltage(V)		Clock (MHz)	Input Signal Range(V)	Analog Switch On Resistance	Channel	Bleed Resistor	PKG	RoHS status	Status
	VDD	VPP-VNN								
ECN3290PL/FN	5	220	10	VNN+10~VPP-10	22Ω (typ.)	8	No	QFJ28 QFN28	C	D
ECN3292TF	5	220	10	VNN+10~VPP-10	19Ω (typ.)	8	No	LQFP48	C	D
ECN3293TF	3.3/5	220	20	VNN+10~VPP-10	19Ω (typ.)	8	Yes (Both side of SW)	LQFP48	C	D

HVMUX (No dedicated high voltage power supplies required)

◆Ultrasound Imaging System/NDT application

Type	VDC (V)	Logic I/F(V)	Clock (MHz)	Input Signal Range(V)	Analog Switch On Resistance	Channel	Bleed Resistor	PKG	RoHS status	Status
ECN32910FN	10~15	3.3/5	30 @5V 20 @3.3V	-100~+100	18Ω (typ.)	16	No	WQFN48	C	D
ECN32911FN	10~15	3.3/5	30 @5V 20 @3.3V	-100~+100	18Ω (typ.)	16	Yes (Both side of SW)	WQFN48	C	D

Notices

1. The information given herein, including the specifications and dimensions, is subject to change without prior notice to improve product characteristics. Before ordering, purchasers are advised to contact Minebea Power Semiconductor Device (MPSD) sales department.
2. Please be sure to read “Precautions for Safe Use and Notices” in the individual brochure before use.
3. Very high reliability is in a use. (such as use in nuclear power control, aerospace and aviation, life-support-related medical equipment, fuel control equipment and various kinds of safety equipment), Please do not use it.
4. In no event shall MPSD be liable for any damages that may result from an accident or any other cause during operation of the user's units according to this data sheets. MPSD assumes no responsibility for any intellectual property claims or any other problems that may result from applications of information, products or circuits described in this data sheets.
5. In no event shall MPSD be liable for any failure in a semiconductor device or any secondary damage resulting from use at a value exceeding the absolute maximum rating.
6. No license is granted by this data sheets under any patents or other rights of any third party or Minebea Power Semiconductor Device Inc.
7. This data sheets may not be reproduced or duplicated, in any form, in whole or in part , without the expressed written permission of Minebea Power Semiconductor Device Inc.
8. The products (technologies) described in this data sheets are not to be provided to any party whose purpose in their application will hinder maintenance of international peace and safety not are they to be applied to that purpose by their direct purchasers or any third party. When exporting these products (technologies), the necessary procedures are to be taken in accordance with related laws and regulations.

ご注意

1. 本資料に掲載した内容は、予告なく変更することがありますのでご了承ください。
2. 製品ご使用の前に「使用上の注意」をよくお読みのうえ、正しくご使用下さい。
3. 極めて高い信頼性が要求される用途（原子力制御用、航空宇宙用、交通機器、ライフサポート関連の医療機器、燃焼制御機器、各種安全機器など）に使用される場合は、特に高信頼性が確保された半導体デバイスの使用及び使用側でフェイルセーフなどを配慮した安全性確保をして下さい。または当社営業窓口にご照会下さい。
4. 本資料に記載された情報、製品や回路の使用に起因する損害または特許権その他権利の侵害に関しては、当社は一切その責任を負いません。
5. 絶対最大定格値を越えてご使用された場合の半導体デバイスの故障及び二次的損害につきましては、弊社はその責任を負いません。
6. 本資料によって第三者またはミネベアパワーデバイス株式会社の特許権その他権利の一部を許諾するものではありません。
7. 本資料の一部または全部を当社に無断で転載または複製する事を堅くお断り致します。
8. 本資料に記載された製品（技術）を国際的平和および安全の維持の妨げとなる使用目的を有する者に再提供したり、またそのような目的に自ら使用したり第三者に使用させたりしないようにお願いします。なお、輸出などされる場合は外為法の定めるところに従い必要な手続きをおとりください。

ホームページ : <https://www.minebea-psd.com/>

URL : <https://www.minebea-psd.com/en>