

MBM600E17F

Preliminary Specification

Silicon N-channel IGBT 1700V F version

FEATURES

- * * Soft switching behavior, low switching loss & low conduction loss :
Soft low-injection punch-through with trench gate IGBT
- * Low driving power due to low input capacitance advanced trench MOS gate.
- * Ultra soft fast recovery diode.
- * Low $R_{th(j-c)}$ & low stray inductance.
- * High thermal fatigue durability

ABSOLUTE MAXIMUM RATINGS ($T_C=25^\circ\text{C}$)

Item	Symbol	Unit	MBM600E17F
Collector Emitter Voltage	V_{CES}	V	1,700
Gate Emitter Voltage	V_{GES}	V	± 20
Collector Current	DC	I_C	600
	1ms	I_{CRM}	1,200
Forward Current	DC	I_F	600
	1ms	I_{FRM}	1,200
Junction Temperature	$T_{vj,op}$	$^\circ\text{C}$	-50 ~ +150
Storage Temperature	T_{stg}	$^\circ\text{C}$	-50 ~ +125
Isolation Voltage	V_{ISO}	V_{RMS}	4,000(AC 1 minute)
Screw Torque	Terminals (M4/M8)	-	2/15 (1)
	Mounting (M6)	-	6 (2)

Notes: (1) Recommended Value $1.8 \pm 0.2 / 15^{+0}_{-3} \text{N}\cdot\text{m}$ (2) Recommended Value $5.5 \pm 0.5 \text{N}\cdot\text{m}$

ELECTRICAL CHARACTERISTICS

Item	Symbol	Unit	Min.	Typ.	Max.	Test Conditions
Collector Emitter Cut-Off Current	I_{CES}	mA	-	5	-	$V_{CE}=1,700\text{V}, V_{GE}=0\text{V}, T_{vj}=25^\circ\text{C}$
			-	12	40	$V_{CE}=1,700\text{V}, V_{GE}=0\text{V}, T_{vj}=150^\circ\text{C}$
Gate Emitter Leakage Current	I_{GES}	nA	-500	-	+500	$V_{GE}=\pm 20\text{V}, V_{CE}=0\text{V}, T_{vj}=25^\circ\text{C}$
Collector Emitter Saturation Voltage	$V_{CE(sat)}$	V	-	2.0	TBD	$I_C=600\text{A}, V_{GE}=15\text{V}, T_{vj}=150^\circ\text{C}$
Gate Emitter Threshold Voltage	$V_{GE(th)}$	V	4.1	5.5	7.1	$V_{CE}=10\text{V}, I_C=60\text{mA}, T_{vj}=25^\circ\text{C}$
Input Capacitance	C_{ies}	nF	-	43.5	-	$V_{CE}=10\text{V}, V_{GE}=0\text{V}, f=100\text{kHz}, T_{vj}=25^\circ\text{C}$
Internal Gate Resistance	$R_{G(int)}$	Ω	-	5.3	-	$V_{CE}=10\text{V}, V_{GE}=0\text{V}, f=100\text{kHz}, T_{vj}=25^\circ\text{C}$
Turn On Delay Time	$t_{d(on)}$	μs	-	0.8	-	$V_{CC}=900\text{V}, I_C=600\text{A}$
Rise Time	t_r		-	0.2	-	$L_S=100\text{nH}$ (3)
Turn Off Delay Time	$t_{d(off)}$		-	1.4	-	$R_G(\text{on/off})=5.6/5.6\Omega$ (3)
Fall Time	t_f	μs	-	1.9	-	$V_{GE}=\pm 15\text{V}, T_{vj}=150^\circ\text{C}$
Peak Forward Voltage Drop	V_F	V	-	1.6	TBD	$I_F=600\text{A}, V_{GE}=0\text{V}, T_{vj}=150^\circ\text{C}$
Reverse Recovery Time	t_{rr}	μs	-	1.0	-	$V_{CC}=900\text{V}, I_C=600\text{A}$
Turn On Loss	E_{on}	J/P	-	0.19	-	$L_S=100\text{nH}$ (3)
Turn Off Loss	E_{off}	J/P	-	0.51	-	$R_G(\text{on/off})=5.6/5.6\Omega$ (3)
Reverse Recovery Loss	E_{rr}	J/P	-	0.30	-	$V_{GE}=\pm 15\text{V}, T_{vj}=150^\circ\text{C}$
Thermal Impedance	IGBT	$R_{th(j-c)}$	-	-	0.032	Junction to case
	FWD	$R_{th(j-c)}$	-	-	0.047	
Contact Thermal Impedance	$R_{th(c-f)}$	K/W	-	0.016	-	Case to fin (grease= $1\text{W}/(\text{m}\cdot\text{K})$) (per 1 arm)

Notes:(3) L_S and R_G are the test condition's values for evaluation of the switching times, not recommended value.Please, determine the suitable R_G value after the measurement of switching waveforms (overshoot voltage, etc.) with appliance mounted.


- * Please contact our representatives at order.
- * For improvement, specifications are subject to change without notice.
- * For actual application, please confirm this spec sheet is the newest revision.
- * ELECTRICAL CHARACTERISTIC items shown in above table are according to IEC 60747-2 and IEC 60747-9.

MBM600E17F

Preliminary Specification


OUTLINE DRAWING

Unit in mm




Weight : 900g

CIRCUIT DIAGRAM



MBM600E17F


Preliminary Specification



$$V_{CE}(sat)[V] = a_3 \cdot |I_c|^3 + a_2 \cdot |I_c|^2 + a_1 \cdot |I_c| + a_0$$

Temp.[°C]	$V_{GE}[V]$	a_3	a_2	a_1	a_0
25	15	1.55E-09	-3.39E-06	3.37E-03	6.55E-01


Collector Current vs. Collector to Emitter Voltage



$$V_{CE}(sat)[V] = a_3 \cdot |I_c|^3 + a_2 \cdot |I_c|^2 + a_1 \cdot |I_c| + a_0$$

Temp.[°C]	$V_{GE}[V]$	a_3	a_2	a_1	a_0
150	15	1.53E-09	-3.33E-06	3.95E-03	5.17E-01

Collector Current vs. Collector to Emitter Voltage




$$V_F[V] = a_3 \cdot |I_F|^3 + a_2 \cdot |I_F|^2 + a_1 \cdot |I_F| + a_0$$

Temp.[°C]	a_3	a_2	a_1	a_0
25	1.66E-09	-3.68E-06	3.14E-03	6.32E-01
150	1.42E-09	-3.30E-06	3.38E-03	4.55E-01

Forward Voltage of free-wheeling diode

MBM600E17F


Preliminary Specification



$$E [J] = a_3 \cdot |I_c|^3 + a_2 \cdot |I_c|^2 + a_1 \cdot |I_c| + a_0$$

Temp.[°C]	a_3	a_2	a_1	a_0
25	-1.76E-11	5.41E-08	1.46E-04	1.09E-02
150	1.00E-10	-9.49E-08	3.07E-04	1.82E-02


Turn-on loss vs. Collector current



$$E [J] = a_3 \cdot |I_c|^3 + a_2 \cdot |I_c|^2 + a_1 \cdot |I_c| + a_0$$

Temp.[°C]	a_3	a_2	a_1	a_0
25	1.63E-10	-3.78E-07	7.49E-04	2.80E-02
150	2.81E-10	-6.86E-07	1.08E-03	4.86E-02


Turn-off loss vs. Collector current



$$E [J] = a_3 \cdot |I_c|^3 + a_2 \cdot |I_c|^2 + a_1 \cdot |I_c| + a_0$$

Temp.[°C]	a_3	a_2	a_1	a_0
25	7.92E-11	-2.33E-07	3.66E-04	5.47E-03
150	1.85E-10	-5.51E-07	7.01E-04	3.76E-02


Reverse Recovery loss vs. Forward current




Switching time vs. Collector Current

MBM600E17F


Preliminary Specification



Turn-on loss vs. Gate Resistance





Turn-off loss vs. Gate Resistance





Reverse Recovery loss vs. Gate Resistance

MBM600E17F

Preliminary Specification




Reverse Bias Safe Operation Area (RBSOA)




Reverse Recovery Safe Operation Area (RRSOA)

MBM600E17F

Preliminary Specification



Capacitance vs. Collector to Emitter Voltage



Transient Thermal Impedance Curve

Material declaration

Please note the following materials are contained in the product, in order to keep characteristic and reliability level.

Material	Contained part
Lead (Pb) and its compounds	Solder

MBM600E17F

Preliminary Specification

Minebea POWER SEMICONDUCTORS

Notices

1. Since mishandling of semiconductor devices may cause malfunctions, please be sure to read "Precautions for Safe Use and Notices" in the individual brochure before use.
2. When designing an electronic circuit using semiconductor devices, please do not exceed the absolute maximum rating specified for the device under any external fluctuations. And for pulse applications, please also do not exceed the "Safe Operating Area (SOA)".
3. Semiconductor devices may sometimes break down by accidental or unexpected surge voltage, so please be careful about the safety design such as redundant design and malfunction prevention design which don't cause the damage expand even if they break down.
4. In cases where extremely high reliability is required (such as use in nuclear power control, aerospace and aviation, traffic equipment, life-support-related medical equipment, fuel control equipment and various kinds of safety equipment), safety should be ensured by using semiconductor devices that feature assured safety or by means of users' fail-safe precautions or other arrangement. Or consult with MPSD's sales department staff. (When semiconductor devices fail, as a result the semiconductor devices or wiring, wiring pattern may smoke, ignite, or the semiconductor devices themselves may burst.)
5. A semi-processed article is done now using solder which contains lead inside the semiconductor devices. There is possibility of the regulation substance depend on the applied models, so please check before using.
6. This specification is a material for component selection, which describes specifications of power semiconductor devices (hereinafter referred to as products), characteristic charts, and external dimension drawings.
7. The information given herein, including the specifications and dimensions, is subject to change without prior notice to improve product characteristics. Before ordering, purchasers are advised to contact with Minebea power semiconductor sales department for the latest version of this data sheets.
8. For handling other than described in this manual, follow the handling instructions (IGBT-HI-00002).

-
- For inquiries relating to the products, please contact nearest representatives that is located "Inquiry" portion on the top page of a home page.
-

Minebea power semiconductor home page address

<https://www.minebea-psd.com/>

<https://www.minebea-psd.com/en/>

MBM600E17F

Preliminary Specification

Minebea POWER SEMICONDUCTORS

Usage

1. MPSD warrants that the MPSD products have the specified performance according to the respective specifications at the time of its sale. Testing and other quality control techniques of the MPSD products by MPSD are utilized to the extent MPSD needs to meet the specifications described in this document. Not every device of the MPSD products is specifically tested on all parameters, except those mandated by relevant laws and/or regulations.
2. Following any claim regarding the failure of a product to meet the performance described in this document made within one month of product delivery, all the products in relevant lot(s) shall be re-tested and re-delivered. The MPSD products delivered more than one month before such a claim shall not be counted for such response.
3. MPSD assumes no obligation nor makes any promise of compensation for any fault which should be found in a customer's goods incorporating the products in the market. If a product failure occurs for reasons obviously attributable to MPSD and a claim is made within six months of product delivery, MPSD shall offer free replacement or payment of compensation. The maximum compensation shall be the amount paid for the products, and MPSD shall not assume responsibility for any other compensation.
4. MPSD reserves the right to make changes in this document and to discontinue mass production of the relevant products without notice. Customers are advised to confirm specification of the product of inquiry before purchasing of the products that the customer desired. Customers are further advised to confirm before purchasing of such above products that the product of inquiry is the latest version and that the relevant product is in mass production status if the purchasing of the products by the customer is suspended for one year or more.
5. When you dispose of MPSD products and/or packing materials, comply with the laws and regulations of each country and/or local government. Conduct careful preliminary studies about environmental laws applying to your products such as RoHS, REACH. MPSD shall not assume responsibility for compensation due to contravention of laws and/or regulations.
6. MPSD shall not be held liable in any way for damages and infringement of patent rights, copyright or other intellectual property rights arising from or related to the use of the information, products, and circuits in this document.
7. No license is granted by this document of any patents, copyright or other intellectual property rights of any third party or of MPSD.
8. This document may not be reprinted, reproduced or duplicated, in any form, in whole or in part without the express written permission of MPSD.
9. You shall not use the MPSD products (technologies) described in this document and any other products (technologies) manufactured or developed by using them (hereinafter called "END Products") or supply the MPSD products (technologies) and END Products for the purpose of disturbing international peace and safety, including (i) the design, development, production, stockpiling or any use of weapons of mass destruction such as nuclear, chemical or biological weapons or missiles, (ii) the other military activities, or (iii) any use supporting these activities. You shall not sell, export, dispose of, license, rent, transfer, disclose or otherwise provide the MPSD products (technologies) and END Products to any third party whether directly or indirectly with knowledge or reason to know that the third party or any other party will engage in the activities described above.
When exporting, re-export transshipping or otherwise transferring the MPSD products (technologies) and END Products, all necessary procedures are to be taken in accordance with Foreign Exchange and Foreign Trade Act (Foreign Exchange Act) of Japan, Export Administration Regulations (EAR) of US, and any other applicable export control laws and regulations promulgated and administered by the governments of the countries asserting jurisdictions over the parties or transaction.